

AI Stereo Vision People Counter VS125 Indoor Series

Milesight



VS125 Indoor Series is a professional people counting sensor based on deep learning AI and Binocular Stereo Vision technology. This sensor possesses an impressive accuracy of up to 99.8% in people counting, and it delivers exceptional performance even in low light environment and total darkness. In addition, it can perform rich attribute recognition, including gender, children, and staff. It is designed with privacy protections that comply with GDPR.

VS125 Indoor Series offer various connectivity options (Cellular and PoE) for seamless connectivity and efficient space management across applications. Additionally, it provides rich interfaces for versatile connection options (RS485/DO/DI), expanding the possibilities for integration and customization.

The device can be easily installed, making it ideal in retail stores, malls, offices, subways, and other locations.

◆ Features

Highly-efficient Sensing Ability

- Up to 99.8% people counting accuracy with AI and stereo vision technology
- Great lighting adaptability that allows it to work well in low light environments and complete darkness
- With high ceiling mounting of up to 6m, support automatic tilt correction and automatic infrared light adjustment (Standard Version)
- Supports a minimum installation height of 1.9 meters and provides a detection range of up to 40

square meters at an installation height of 3.5 meters (Low&Wide Version)

- Customer-defined preview privacy settings, no data with personal information is transmitted, complies with GDPR
- Supports line crossing people counting, regional people counting and dwell time detection
- Rich attribute recognition capabilities, including gender, group counting, children and staff identification etc, provide deeper insights
- Supports heat map functionality for analyzing foot traffic intensity and distribution
- Support Multi-Device Stitching which enables the linking of multiple devices, allowing for up to 16-device stitching to expand coverage
- Supports local data storage and data retransmission to ensure secure data collection

Rich Connectivity Options

- Provide multiple connectivity options (PoE, Cellular)
- Supports RS485/DI/DO multiple interfaces and has strong scalability
- Allows quick and easy management via Milesight DeviceHub and the Milesight Development Platform
- High compatibility of data transmission with HTTP(s)/MQTT(s) protocol and API, supports customized push content methods

◆ Specifications

Version	Standard Version		Low-and-Wide Version	
Model Name	VS125-P	VS125-L0BEU	VS125-LW-P	VS125-LW-L0EGL
Sensor				
Sensor	2 × 4MP Sensor (2688 × 1520)		2 × 5MP Sensor (2592 × 1744)	
Installation Height	2.2 ~ 6m		1.9 ~ 3.5m	
FoV	101° Horizontal, 70° Vertical		130° Horizontal, 117° Vertical	
Recognition Rate	Up to 99.8%			
Required Illumination	0 lux with iR illuminators On			
Advanced Function				
Bi-Directional People Counting	Up to 4 detection lines for bi-directional people counting			
U-turn Filtering	Filter redundant counting of people wandering in the bi-directional people counting areas			
Regional People Counting & Dwell Time Detection	Up to 4 detection areas (up to 10 decagon for each area) for regional people counting and dwell time detection			
Children/Adult Differentiation	Support (Installation Height: 2.2 ~ 4m)		Support (Installation Height: 1.9 ~ 3.3m)	
Staff Detection				
Gender Recognition				
Group Counting	Support			

Heat Map	Support			
Multi-Device Stitching	Support up to 16 devices stitching to expand coverage			
Validation	8GB			
Data Retransmission	Support 8 × 50000 data retransmission packets			
Local Storage	Stores up to one million data records and supports exporting CSV files			
Data Transmission				
Ethernet				
Ethernet Port	1 × RJ45 10/100 Mbps (PoE PD)	1 × RJ45 10/100 Mbps	1 × RJ45 10/100 Mbps (PoE PD)	1 × RJ45 10/100 Mbps
Network Protocol	MQTT(s), HTTP(s), 802.1x, SSH, NTP, etc.	MQTT(s), HTTP(s), SSH, NTP, etc.	MQTT(s), HTTP(s), 802.1x, SSH, NTP, etc.	MQTT(s), HTTP(s), SSH, NTP, etc.
Ethernet Isolation	1.5 kV RMS	-	1.5 kV RMS	-
Cellular				
Antenna	-	Internal Antenna	-	Internal Antenna
Network	-	4G LTE (CAT1)	-	4G LTE (CAT1)
Frequency Band	-	LTE-FDD: B1/B3/B5/B7/B8/B20/B28 for EMEA+Australia/New Zealand	-	LTE-FDD: B1/2/3/4/5/7/8/12/13/18/19/20/25/26/28/66 LTE-TDD: B34/38/39/40/41
SIM Slot	-	1 x Nano SIM (4FF) Slot, 1.8V/3V	-	1 x Nano SIM (4FF) Slot, 1.8V/3V
Other Interfaces				
Power Connector	1 × DC Jack Connector			
DI/DO	1/2			
Serial Interface	1 × RS485 (Under Development)			
Wi-Fi	IEEE 802.11 b/g/n, 2.4GHz (AP Mode for configuration)			
Button	1 × Reset/Wi-Fi Button			
LED Indicators	1 × RGB LED indicator			
Physical Characteristics				
Power Supply	802.3af PoE or DC 12V/1A	DC 12V/1A	802.3af PoE or DC 12V/1A	DC 12V/1A
Power Consumption	Avg. 5.9W Max. 11.1W	Avg. 5.1W Max. 10W	Avg. 6.9W Max. 12W	Avg. 6.5W Max. 12W
Operating Temperature	-20°C ~ 50°C		-20°C ~ 60°C	
Relative Humidity	0 ~ 95% (Non-condensing)			

Ingress Protection	IP40			
Dimension	185 × 85 × 34 mm (7.26 × 3.35 × 1.34 in)			
Weight	275g	272g	284.4g	280.9g
Color	White or Black (Optional)			
Installation	Ceiling Mounting, Extended Ceiling Mounting & Lintel Mounting (with Optional Multifunctional Bracket)			
Approvals				
Regulatory	CE, FCC	CE	CE, FCC	
Environment	RoHS			

◆ Detection Area

Standard Version:

Installation Height (m)	Detection Area(m)
2.2	1.21 × 0.7
2.5	1.94 × 1.12
3.0	3.16 × 1.82
3.5	4.37 × 2.52
4.0	5.58 × 3.22
4.5	6.80 × 3.92
5.0	8.01 × 4.62
5.5	9.23 × 5.32
6.0	10.44 × 6.02

Low-and-Wide Version:

Installation Height (m)	Detection Area(m)
1.9	0.86 × 0.65
2.0	1.28 × 0.98
2.2	2.14 × 1.63
2.5	3.43 × 2.61
3.0	5.57 × 4.24
3.5	7.71 × 5.87

◆ Dimensions (mm)

